



Globestock Engineering Ltd.

Manufacturers of Safety & Fall Arrest Equipment

Mile Oak Industrial Estate, Maesbury Road, Oswestry, Shropshire SY10 8GA

Tel: 01691 654966

Fax: 01691 661726

e-mail: info@globestock.co.uk

<http://www.globestock.co.uk>

G-STOP 7-14m



The G-Stop is a retractable type fall arrester fitted with 5mm diameter steel cable. It is manufactured from precision machined components. Internal components are of Bronze, Stainless Steel and Aluminium to ensure reliability in the harshest of environments, including offshore and mining applications. It offers full protection and complete mobility to the user in areas where there is a danger of falling.


Should a fall occur, cable is pulled out of the block at an accelerating rate. When a cable speed of approximately 1.5 m/sec is reached, the braking mechanism is activated arresting the fall quickly and smoothly, exerting minimal forces on the body. When the load is released the cable retracts into the block.

Use mounted vertically above the user or in roofing and horizontal applications in conjunction with a suitable anchorage.

FEATURES

- New durable aluminum housing.
- Proven fall arrest mechanism.
- Improved wear resistance, durability and rope life.
- Steel Cable length: 7 & 14.
- Stopping distance: between 0.6 & 1.0 m.
- Unit weight: 9 kg (approx.)

Safe Working Load: 136 kg.

Carries the  mark of approval.

Fully tested to European Standards.

Note: Globestock Ltd reserve the right to change specifications without prior notice